



EPR – Metal Shield Tag


FEATURES

- M-Shield tag is operates effectively with read range of over 10m when attached to metal.
- Rugged construction for high durability.
- Can be attached by screws with the help of two holes.
- Can also be provided with Adhesive tape for easy attachment.

APPLICATIONS

- Due to high read range, M-Shield can be effectively used in asset tracking, Ware house management, Containers and Railway Coaches identification.
- Factory automation, Automotive & Security purpose.

Chip Type:	UHF Class 1 Gen 2, Alien Higgs 3	
	EPC 96 bit extendable up to 480 bits	
	User Memory 512 bit	
	Data retention of 50 years	
	Write endurance 100.000 cycles	
Mechanical:	Dimension	53 x 53 x 10mm
	Material	ABS
	Colour	Blue 25 g
	Weight	
Electrical:	865-868MHz, (902-928MHz also available on request)	
	Operating Frequency	Passive (battery-less transponder)
	Operating mode	
Ingress Protection:	IP67	
Thermal:	Storage Temp.	-40°C to +85°C
	Operating Temp.	-40°C to +85°C
Part Number:	EPR317V3	
Options:	Available with:	
	Other IC type on request	
	Other plastic material and colours	
	Adhesive backing for easy mounting (indoor application)	




Tag Placement

- ✚ M-Shield is polarized perpendicular to TTF logo.
- ✚ Place the tag in such a way that most of its bottom area comes in direct contact with metal. Ensure that there is no hindrance between the tag and the reader antenna.
- ✚ Reader antenna should be perpendicular to the axis of tag hole as shown in below figure:

Correct way




Antenna



Wrong way




Antenna







Frequency v/s Read Range Graph



Angular Sensitivity

M-Shield Tag Angular Sensitivity

(Relative Read Range vs. Orientation)



Tag is rotated in the X-Y plane about the z axis